

# Rally West Motorsports Association

## Section 3.0 - Group 5

The intention of these rules is to encompass the American group 5 class in order to allow more American competitors as well as to allow regional competitors to rally competitively a wider selection of vehicles not currently allowed in the series.

3.1 Definition: Vehicles must be 2 wheel drive models sold globally in minimum quantities of 1000, which meet the requirements of NRR II.c, II.d and the following.

3.2 Drive configuration must remain as originally manufactured.

3.3 Engine: Engine is unrestricted, but must be based on an engine block offered by the vehicle manufacturer either as production in any vehicle or high performance replacement

3.4 Adjusted displacement: The adjusted displacement must be no greater than 5100 cc. using the following multipliers:

Pushrod engines	0.8 x actual displacement
Turbo/ Supercharged	1.7 x actual displacement
Rotary	1.8 x actual displacement

3.5 Bodywork: Exterior pieces (all components licked by the airstream) must be visually similar to the original item, including bumpers. Except for doors and roof, bolt-on body pieces may be constructed of an alternate material. A and B pillars must remain original. Original floor pan must remain and may be modified only to the extent necessary to accommodate allowed alternate components, but in all cases, must be a complete metal separation between the passenger compartment and engine. Roof mounted commercially available cooling vents are allowed. Fenders may be modified to the extent necessary to provide tire clearance, flares may be added.

3.6 Other restrictions:

(a) No type or form of electronic control is permitted for: Suspension, Steering, Braking, Gear change/clutch (Excluding automatic transmission), or Differential.

(b) Simple engine cut operating during a mechanically activated gear change is permitted.

(c) Sequential gear change mechanisms are not permitted (excluding automatic transmissions)

3.7 Mechanical components: Unrestricted other than above.

3.8 Wheels: Any diameter or width is allowed provided that they are covered by the fenders or flares.